



Preproduction model shown. Actual production model may vary.
Available early 2020.

CUSTOMER BENEFITS

- Customers can open their convertible top using either a switch inside the vehicle or with their key fob
- The convertible top can be operated at speeds up to 30 mph and takes approximately 17 seconds to open or close

CONVERTIBLE TOP CONTROLS

Quickly and Conveniently Open and Close the Convertible Top

OVERVIEW

Convenient controls inside the vehicle and on the key fob allow customers to quickly and easily open their 2020 Chevrolet Corvette Stingray convertible top. When they want to close the convertible top, they can do so using the same control inside the vehicle.

HOW IT WORKS

Customers can use a switch inside the vehicle to open or close the convertible top. Additionally, they can use their key fob to open the convertible top from outside the vehicle.

Opening the Convertible Top

There are two ways the customer can open the convertible top:

1. Using a switch inside the vehicle, located on the driver's side door panel:

The vehicle must be in ON, ACCESSORY or RETAINED ACCESSORY POWER mode and moving approximately 30 mph or less* to open the convertible top with the interior switch.

- ♦ Find the switch on the driver's side door panel, located near the driver- and passenger-side power window switch
- ♦ Press and hold the switch to initiate the opening. There will be a slight delay before the windows lower and the convertible top begins to open
- ♦ Continue to hold the switch until the opening motion is complete. It will take approximately 17 seconds

Note: If the customer releases the switch before the motion is complete, it will stop in progress and remain partially open. The customer should press and hold the switch again to continue opening the top.

- ♦ When complete, a "Folding top motion complete" message will appear in the Driver Information Center (DIC) and a chime will sound

2. Using the vehicle's key fob:

The key fob must be within approximately 197 ft. of the vehicle in order to open the convertible top. The vehicle should be in PARK and the vehicle is OFF (not in Retained Accessory Power) in order to open it this way.

- ♦ Using the vehicle's key fob, press and release the UNLOCK button, and then quickly press and hold the FOLDING TOP button. There will be a slight delay before the windows lower and the convertible top begins to open
- ♦ Continue to hold the FOLDING TOP button until the opening motion is complete. It will take approximately 17 seconds

Note: If the customer releases the key fob button before the motion is complete, it will stop in progress and remain partially open. To continue opening the top, the customer must press the UNLOCK button again, and then press and hold the FOLDING TOP button.

- ♦ The exterior lights will flash and a chime will sound to let you know the motion is complete

* See "Vehicle Speed When Using Convertible Top" for additional information.

For GM dealership personnel use only. Not intended for advertising purposes. GM reserves the right to make changes at any time, without notice, in prices, colors, materials, equipment, features, specifications and availability. Product information is preliminary and reflects approved content at time of publishing.



Preproduction model shown. Actual production model may vary.
Available early 2020.

CONVERTIBLE TOP CONTROLS

Closing the Convertible Top

The customer can use the switch located inside the vehicle on the driver's side door panel to close the convertible top.

To close the convertible top, the vehicle must be in ON, ACCESSORY or RETAINED ACCESSORY POWER mode and moving approximately 30 mph or less*.

- ◆ Find the switch on the driver's side door panel, located near the driver- and passenger-side power window switch
- ◆ Lift up on and hold the switch to initiate the closing. There will be a slight delay before the convertible top begins to close
- ◆ Continue to lift up on the switch until the closing motion is complete and the top latches. It will take approximately 17 seconds

Note: If the customer releases the switch before the motion is complete, it will stop in progress and remain partially closed. The customer should lift up on and hold the switch again to continue closing the top.

- ◆ When complete, a "Folding top motion complete" message will appear in the Driver Information Center (DIC) and a chime will sound
- ◆ If the customer continues holding the switch once the top is fully closed, the windows will raise as you continue to hold the switch or until closed

Vehicle Speed When Using the Convertible Top

For safety reasons, use of the convertible top impacts the vehicle's speed.

- ◆ The vehicle must be moving approximately 30 mph or less in order to open or close the convertible top
- ◆ If the vehicle exceeds 30 mph while the convertible top is in the process of opening or closing, it will stop in progress and remain partially open or closed. If this happens, the customer should reduce their speed to approximately 30 mph or less, and then repeat the opening or closing action
- ◆ When the convertible top is fully open, the vehicle's speed is limited to approximately 155 mph

- ◆ The vehicle's speed will be limited to approximately 58 mph anytime the convertible top is not secure (either because it is not fully latched or was left partially opened/closed). If this happens, the customer should reduce their speed to approximately 30 mph or less and completely open or close the convertible top
- ◆ Customers should pay attention to any DIC messages and/or chimes that will alert them of these issues

Accessing the Engine Compartment

In order to access the mid-engine compartment for vehicle service on convertible models, the tonneau cover must be opened. This can be done using the vehicle's key fob.

- ◆ Ensure the vehicle is OFF (not in Retained Accessory Power) and the convertible top is closed and latched
- ◆ Using the vehicle's key fob when it's within 10 ft., press and release the LOCK button, and then quickly press and hold the FOLDING TOP button. A chime will sound, the turn signals will flash and a DIC message will be displayed
- ◆ Continue to hold the FOLDING TOP button until the tonneau cover is open to provide the necessary access to the engine compartment (for some types of service, the engine cover may need to be removed). The exterior lights will flash once the motion is complete
- ◆ To close the tonneau cover once service is complete, the customer should repeat the same motion of pressing the LOCK button, and pressing and holding the FOLDING TOP button
- ◆ The tonneau cover will reverse directions (open or close) each time the customer repeats this process. Also, if it's partially open or closed it may drift down to a near-closed position over time
- ◆ After accessing the engine compartment, make sure the fluid container plugs are properly secured before closing the top

* See "Vehicle Speed When Using Convertible Top" for additional information.



Preproduction model shown. Actual production model may vary.
Available early 2020.

CONVERTIBLE TOP CONTROLS

USAGE TIPS

- ◆ To avoid injury while opening or closing the convertible top, maintain visual contact with the top while it's operating. Customers should also remove all objects that may interfere with the opening or closing
- ◆ Customers should not open or close the convertible top while driving in high wind conditions
- ◆ The windows automatically lower when the convertible top is opened or closed
 - In order to help mitigate wind, the rear window (midglass) does not fully lower. If desired, the customer can raise the rear window once the convertible top is open to help reduce wind noise
- ◆ When the convertible top is open, the audio volume of the radio may briefly mute and then automatically adjust to accommodate for wind noise
- ◆ If the convertible top is partially opened or closed, the customer will not be able to access the rear trunk compartment
- ◆ If the rear trunk compartment access is open, the customer will not be able to open or close the convertible top
- ◆ The key fob may not work as expected to open or close the convertible top if there's interference, such as in a garage, under a power line or when it's near another key fob

FAQs

Why is there a delay when I use the convertible top controls before the top starts opening/closing?

There is a slight delay when you use the interior switch or the key fob to open or close the convertible top to help avoid unintentional operation. This is designed to help prevent you from inadvertently opening the convertible top if, for example, you were only trying to open your windows.

Why can't I close my convertible top using my key fob?

For safety reasons, the key fob cannot be used to close the convertible top. You must be inside the vehicle supervising the motion of the top in order to close it.

Why doesn't my Rear Camera Mirror work when the convertible top is open?

When the convertible top is open, the Rear Camera Mirror (if equipped) display is not available, since the camera is mounted to the roof. Rear Camera Mirror will automatically revert to a traditional inside rearview mirror when the top is open, and then revert back to the Rear Camera Mirror display once the top is closed.

After I opened and closed it a few times, my convertible top controls stopped working. Why?

To protect the mechanisms and the vehicle's battery, the convertible top controls are temporarily disabled after you cycle them multiple times in a row without starting the engine. After about 10 minutes, they should work again.

What is the purpose of the black pillars over the B-pillars?

When the convertible top opens, black closeout panels will automatically deploy to help provide a more seamless appearance and help mitigate wind noise.

Why does the top sag when I leave it partly open?

When the convertible top is left in a partially opened or closed position, it may drift down to a near-closed position over time. This is normal and does not impact its performance.

Will my convertible top open or close in cold temperatures?

It's possible to open the convertible top down to temperatures of 32° F (0° C) and close the top down to temperatures of approximately 14° F (-10° C). If it's too cold, a DIC message will be displayed and the customer should move to a heated indoor area, such as a garage, to operate the top.